

This presentation premiered at WaterSmart Innovations

watersmartinnovations.com



Overcoming Condensate Collection and Use Challenges

WaterSmart Innovations 2012

Diana D. Glawe

Engineering Science Department



TRINITY UNIVERSITY


SAN ANTONIO • 1869

Condensate

Water that collects on a cool surface because the temperature of the surface is below the point at which moisture in the air forms liquid droplets (i.e. dew point)



Air Handling Unit (AHU)




(Source: *San Antonio Condensate Collection and Use Manual for Commercial Buildings*. Pending publication)

How Much Condensate?



How Much Condensate?

Example: 154,440 sq ft (727 ton) applied engineering and technology building measured condensate with predictions (747,290 gallons/yr)



(Source: *San Antonio Condensate Collection and Use Manual for Commercial Buildings*. Pending publication)

Condensate Water Quality?

- Slightly acidic
- Theoretically pure water
- Contaminants
 - Whatever is picked up along the flow path
 - Elements
 - Microbes
 - Particulate



Benefits of Reclaimed Condensate

- Economic benefit for building owner
- Reduce burden on central water utility systems
- Water savings, energy savings, CO₂ savings

Key Challenges of Reclaimed Condensate

- Initial investment/payback period
- Achieving an effective design
- Operations and maintenance

Payback Period Equation

$$\textit{Payback period} = \frac{\textit{Incremental investment}}{\textit{Annual savings}}$$

- Incremental investment = initial cost – mandatory costs – rebates & incentives
- Annual savings
 - Scheduled water rate increases shorten period
 - High discount rate of borrowing capital lengthens payback
 - Green finance programs could reduce financial burden

Payback Period – Application

- Cooling tower make-up water is typically BEST application
 - Low initial cost
 - Easy implementation
 - Cool and pure water a plus
 - Low maintenance

Example: Building producing 224,511 gallons per year. Cost to install retrofit system for cooling tower makeup water was \$2,272 materials (pipes and pumps) plus \$750 labor. SAWS rebate 50%. Incremental investment \$1,511. Payback period 16 months. No water treatment beyond that already existing for cooling tower water. No overflow and no storage requirements. Maintain air seal and pump (if applicable).

Payback Period - Applications


- Other applications include
 - Irrigation
 - Water features
 - Toilet flushing
 - Car washing
 - Process water
 - Trap primers
 - Drinking water – ONLY with specialized system and ONLY if permitted in jurisdiction

Other Priorities - Applications

- Other priorities and related payback
 - Bypass drought restrictions
 - Environmental stewardship

Example: Based on analysis of energy that City Public Services (CPS) must provide to support San Antonio Water System (SAWS) operation. A building reclaiming one million gallons of water for use on-site saves the City of San Antonio 4141 kWh/yr and reduces carbon emissions by 2.84 metric tons per year.


Effective Design – Drain Line Air Seal



(Source: *San Antonio Condensate Collection and Use Manual for Commercial Buildings*. Pending publication)

Air Seals : Standard P-trap


- Isolates air handling unit
- Minimizes pipe wet time
- Maintenance access point
- Trap configurations
 - Draw-thru trap
 - Blow-thru trap
- Standard traps incur
 - High maintenance
 - High failure rate




(Source: Brusha, Ronald F. "Condensate Traps for Cooling Coils." HPAC Engineering, Oct 2001)

Alternatives to Standard P-trap


P-trap




P-trap with additions



Condensate pump in drain pan




Pneumatic air seal



- Auxiliary (backup) drainage system and/or warning alarm recommended for all air seal designs

Effective Design – Treatment Train

- Depends on reclaimed water source(s)
- Depends on reclaimed water application



(Source: Adapted from Mechell et. al, *Rainwater Harvesting: System Planning*. 2010)

Effective Design - Optimization

- Match application to water quantity
 - Predict quantity
 - Storage tank sizes to provide 50% water demand per annum (SAWS)
 - Consider commingling other reclaimed water sources
- Consider treatment requirements
 - Treatment train options
 - Monitoring and reporting requirements
- Consider operation and maintenance

Effective Design – Automated Monitoring

- Drip pan overflow alarm
- Condensate meter data collection
- Make-up water meter data collection
- Water quality sensors in treatment train
- Make it difficult for system failures to go unnoticed

Operation and Maintenance -Scheduled Maintenance Program

- Start with commissioning during installation!
- Document operating procedures – checklist
- AHU: air filter, cooling coils, drain pan
- Drain seal
- Piping, pumps, and valves
- Storage Tank: overflow and makeup water control
- Backflow valve inspection (required annually by city code)
- Water treatment filters, lamps, etc.
- Water quality tests

Overcome Challenges - Continued

- “Policy”
 - Codes & standards
 - Water rates
 - Incentives
- Education
 - Optimize implementation
 - Operation & maintenance
- Technology advancements
 - Design
 - Equipment
 - Processes

Codes and Standards

(jurisdiction - city, state, federal policy)


- San Antonio City Code 34-274.1
 - Information bulletin 163
 - Single condensate discharge point
 - Discharged to sanitary drain if not used
- Adopt national/international codes and standards
 - International Green Construction Code
 - ASHRAE Standard 189.1
 - Green Plumbing and Mechanical Code Supplement

Water Rates & Incentives (water provider policy)

- Increasing water rates make reclaiming water attractive
- San Antonio Water System (SAWS) rebates for commercial, institutional, and industrial users
 - \$400 per acre-foot water saved over 10 years
 - Up to 50% of installed cost
- Fee avoidance (incidental)
- Free meter in support of metering program

Condensate User Manual (addressing the educational aspect)

- In collaboration with San Antonio Water System (SAWS)
- Design through maintenance
- Public domain
- Currently in “Proof Copy” for review
- Feedback requested by end of October



Quality & Quantity Research at Trinity (addressing the technology aspect)

Funded by Associated Colleges of the South Grant*

ELEMENTS

MICROBES

CHARACTERISTICS

MICROSOFT ACCESS
DATABASE

(prediction models)

GRAVITY DRIVEN PD METER
TESTS

Collaboration with SAWS

METER PILOT PROGRAM
(feeds DATABASE)

*Faculty: D. Glawe (ENGR), F. Healy (BIO), M. Bushey (CHEM)

Students: J. Erdman, C. Edge, E. Jayamanne (ENGR) H. Duong (CSCI) Class (CHEM)

Quantity Data

MICROSOFT ACCESS
DATABASE
(prediction models)

GRAVITY-DRIVEN PD
METER TESTS

Accuracy?

METER PILOT PROGRAM
(feeds DATABASE)

Automated
Data




Data


Report

Prediction Model

Date	Basin 1	Basin 2	Basin 3	Basin 4
8-Jun-08		27,829,600		33,101,500
15-Jun-08		27,869,200		33,908,100
22-Jun-08		27,910,500		34,711,800
29-Jun-08		27,935,000		35,428,700
7-Jul-08		27,942,300		35,961,800
13-Jul-08		27,966,300		36,549,300
20-Jul-08		28,003,700		37,265,700
27-Jul-08		28,044,000		37,937,600



21-Dec-08	28,237,600	38,648,900
28-Dec-08	28,237,600	39,503,400
4-Jan-09	28,237,600	40,179,300
11-Jan-09	28,237,600	41,239,200
18-Jan-09	28,237,600	41,895,000
25-Jan-09	28,237,600	42,570,500
1-Feb-09	28,237,600	43,434,000
8-Feb-09	28,237,600	43,975,600
15-Feb-09	28,237,600	44,453,700
22-Feb-09	28,237,600	44,883,000
1-Mar-09	28,664,800	45,217,100
		45,600,100
		45,987,700
		46,308,600
		46,552,800
		46,867,100
		47,080,100
		47,313,200
		47,600,500
		47,896,500
		48,106,300
		48,431,500
		48,686,300
		49,032,500
		49,131,900
		49,154,300
		49,363,300
		49,635,600
		49,688,100



Questions

Diana D. Glawe

Associate Professor

Trinity University

San Antonio, TX 78209

dglawe@trinity.edu

210-999-7515

